

Low Voltage Battery 5 to 20 kWh

Ai-LB-G3 Series



Models:
ASW5120-LB-G3



Optimal performance

- Low self and standby consumption
- Enhanced SOC measurement accuracy for optimal battery management
- Supports up to 1C charge / discharge rate



Safe & Reliable

- IP66 rated design for indoor and outdoor use
- Designed in accordance with global safety standards
- Integrated fire suppression system
- Smarter and safer battery management system for precise diagnostics
- Integrated MOSFET and dual fuse protection for superior safety and reliability







User-friendly

- Stackable up to 4 modules, 20.48 kWh per tower
- Elegant design with concealed cable management
- Compact, lightweight modules for easier handling and installation
- 5 selections for operating (LED) indicator via Solplanet App

Technical Datasheet

ASW5120-LB-G3

System Data	Module number				
	Cell type	LiFePO4			
	Rated capacity	100 Ah			
	Nominal energy ¹	5.12 kWh	10.24 kWh	15.36 kWh	20.48 kWh
	Usable energy ²	4.86 kWh	9.72 kWh	14.59 kWh	19.45 kWh
	Nominal battery voltage	51.2 V			
	Battery voltage range	40 V ~ 58.4 V			
	Recommended charge/discharge current	60 A	120 A	180 A	210 A
	Max. charge / discharge current	100 A	200 A	210 A	210 A
	Rated charge / discharge power	3.07 kW	6.14 kW	9.22 kW	10.75 kW
Max. charge / discharge power	5.12 kW	10.24 kW	10.75 kW	10.75 kW	
General Data	Dimensions (W/D/H)	630*185*320 mm	630*185*640 mm	630*185*960 mm	630*185*1280 mm
	Module Weight	46.0 kg	92.0 kg	138.0 kg	184.0 kg
	Base weight	2.6 kg			
	Installation location	Indoor / Outdoor			
	Mounting method	Floor mounted / Wall mounted			
	Operating temperature range	Charging: -8 °C ~ 58 °C Discharging: -18 °C ~ 58 °C			
	Storage temperature range	-20°C ~ 60°C			
	Cooling concept	Natural convection			
	Protective class	II			
	Degree of protection	IP66			
	Relative humidity	5 % ~ 95 % RH, non-condensing			
	Max. operating altitude	4000 m (> 3000 m derating)			
	Communication	CAN			
	Certification	IEC 62619, IEC 62040, IEC 63056, IEC 61000, IEC 60730			
	Life cycle ³	6000 times			
Round-trip efficiency	≥ 95 %				

1. Nominal energy is defined under the following conditions: battery voltage 40 ~ 58.4V, 0.5C charge & discharge at +25 °C.

2. Usable energy is defined under the following conditions: 0.5C charge & discharge at +25 °C, 95 % DOD.

3. Life cycle is defined under the following conditions: 0.5C charge & discharge at 25 °C (One cycle a day), 90 % DOD, 70 % EOL.

*For reference only. Please refer to the official release for final content.

Version: Nov 2024

